



## DIN 7980

Podkładki sprężyste do śrub z łbem walcowym



d	do gwintu	d2 max.	h min.	s
3,0	M3	5,6	2,0	1,0
3,5	M3,5	6,1	2,0	1,0
4,0	M4	7,0	2,4	1,2
5,0	M5	8,8	3,2	1,6
6,0	M6	9,9	3,2	1,6
8,0	M8	12,7	4,0	2,0
10,0	M10	16,0	5,0	2,5
12,0	M12	18,0	5,0	2,5
14,0	M14	21,1	6,0	3,0
16,0	M16	24,4	7,0	3,5
18,0	M18	26,4	7,0	3,5
20,0	M20	30,6	9,0	4,5
22,0	M22	32,9	9,0	4,5
24,0	M24	35,9	10,0	5,0
27,0	M27	38,9	10,0	5,0
30,0	M30	44,1	12,0	6,0

Materiał	Opakowanie
A2 / A4	1000
A2 / A4	1000
A2 / A4	1000
A2 / A4	1000
A2 / A4	1000
A2 / A4	1000
A2 / A4	500
A2 / A4	500
A2 / A4	200
A2 / A4	200
A2 / A4	200
A2 / A4	100
A2 / A4	100
A2 / A4	100
A2 / A4	100